

Cyprium Collection -
Doors - **LiftSlide Door**

Size Charts

LiftSlide Door

Panels	Configuration	Style	Frame Type	Rough Opening	Head Width	Finish Pocket	Rough Opening	Head Width	Finish Pocket
				(3' Panels)	(3' Panels, No Screens)	Width	(4' Panels)	(4' Panels, No Screens)	Width
2	OX or XO	Stacking	Jamb	73 [1854]	10 3/8 [264]	-	97 [2464]	10 3/8 [264]	-
3	OXX or XXO	Stacking	Jamb	106 [2692]	14 1/4 [362]	-	142 [3607]	14 1/4 [362]	-
4	OXXX or XXXO	Stacking	Jamb	139 [3531]	18 1/16 [459]	-	187 [4750]	18 1/16 [459]	-
5	OXXXX or XXXXO	Stacking	Jamb	172 [4369]	21 15/16 [557]	-	232 [5893]	21 15/16 [557]	-
6	OXXXXX or XXXXO	Stacking	Jamb	205 [5207]	25 3/4 [654]	-	277 [7036]	25 3/4 [654]	-
4	OX-XO	Bi-Parting	Jamb	142 3/16 [3612]	10 3/8 [264]	-	190 3/16 [4831]	10 3/8 [264]	-
6	OXX-XXO	Bi-Parting	Jamb	208 3/16 [5288]	14 1/4 [362]	-	280 3/16 [7117]	14 1/4 [362]	-
8	OXXX-XXXO	Bi-Parting	Jamb	274 3/16 [6964]	18 1/16 [459]	-	370 3/16 [9403]	18 1/16 [459]	-
10	OXXXX-XXXXO	Bi-Parting	Jamb	340 3/16 [8641]	21 15/16 [557]	-	460 3/16 [11689]	21 15/16 [557]	-
12	OXXXXX-XXXXO	Bi-Parting	Jamb	406 3/16 [10317]	25 3/4 [654]	-	550 3/16 [13975]	25 3/4 [654]	-
1	PX or XP	Stacking	Single pocket	39 11/16 [1008]	11 1/16 [280]	7 1/16 [179]	51 11/16 [1313]	11 1/16 [280]	7 1/16 [179]
2	PXX or XXP	Stacking	Single pocket	72 11/16 [1846]	12 5/8 [321]	9 5/8 [245]	96 11/16 [2456]	12 5/8 [321]	9 5/8 [245]
3	PXXX or XXXP	Stacking	Single pocket	105 11/16 [2684]	16 1/2 [419]	13 7/16 [342]	141 11/16 [3599]	16 1/2 [419]	13 7/16 [342]
4	PXXXX or XXXXP	Stacking	Single pocket	138 11/16 [3523]	20 5/16 [516]	17 5/16 [440]	186 11/16 [4742]	20 5/16 [516]	17 5/16 [440]
5	PXXXXX or XXXXXP	Stacking	Single pocket	171 11/16 [4361]	24 3/16 [614]	21 13/16 [538]	231 11/16 [5885]	24 3/16 [614]	21 13/16 [538]
6	PXXXXXX or XXXXXXP	Stacking	Single pocket	204 11/16 [5199]	28 1/16 [712]	24 7/8 [631]	276 11/16 [7028]	28 1/16 [712]	24 7/8 [631]
2	PX-XP	Bi-Parting	Dual pocket	75 1/2 [1918]	-	7 1/16 [179]	99 1/2 [2527]	-	7 1/16 [179]
4	PXX-XXP	Bi-Parting	Dual pocket	141 1/2 [3594]	-	9 5/8 [245]	189 1/2 [4813]	-	9 5/8 [245]
4	PXXX-XXXP	Bi-Parting	Dual pocket	207 1/2 [5271]	-	13 7/16 [342]	279 1/2 [7099]	-	13 7/16 [342]
6	PXXXX-XXXXP	Bi-Parting	Dual pocket	273 1/2 [6947]	-	17 5/16 [440]	369 1/2 [9385]	-	17 5/16 [440]
10	PXXXXX-XXXXXP	Bi-Parting	Dual pocket	339 1/2 [8623]	-	21 13/16 [538]	459 1/2 [11671]	-	21 13/16 [538]
12	PXXXXXX-XXXXXP	Bi-Parting	Dual pocket	405 1/2 [10300]	-	24 7/8 [631]	549 1/2 [13957]	-	24 7/8 [631]

Additional configurations and sizes available. Consult your Authorized Loewen Dealer for details.

Panel Height	Rough Opening Height (1" Flush Track)	Rough Opening Height (1 1/2" Flush Track)	Rough Opening Height (Raised Threshold)
84 [2134]	87 15/16 [2234]	88 7/16 [2246]	88 7/16 [2246]
96 [2438]	99 15/16 [2538]	100 7/16 [2551]	100 7/16 [2551]
108 [2743]	111 15/16 [2843]	112 7/16 [2856]	112 7/16 [2856]
120 [3048]	123 15/16 [3148]	124 7/16 [3161]	124 7/16 [3161]
144 [3658]	147 15/16 [3758]	148 7/16 [3770]	148 7/16 [3770]

Additional heights available. Consult your Authorized Loewen Dealer for details.

Note: • O = Fixed
• X = Operating
• P = Pocketing

• The preparation of the rough opening for large openings such as those required by, but not limited to, LiftSlide and Bifold doors have unique requirements. Structural headers that allow for deflection no greater than 1/8" along the unsupported length once the header is fully loaded are required. Special care needs to be taken when installing any unit including transoms above such large opening units.

Loewen is not responsible for site measurements or the determination of structural and architectural requirements for the installation of large opening products such as but not limited to, Liftslide and Bifold doors. Site specifications are the responsibility of building professionals or engineers to determine.