

Multislide Narrow Stile Stacking

Width

Height

Rough Opening		48 1/2 [1232]	69 11/16 [1770]	72 1/2 [1842]	105 11/16 [2684]	138 13/16 [3527]	172 [4369]	205 3/16 [6052]	238 5/16 [6052]	271 1/2 [6896]	144 1/2 [3671]	213 11/16 [5427]	282 13/16 [7184]	352 [8941]	409 [10383]					
System		47 1/2 [1207]	68 11/16 [1744]	71 1/2 [1816]	104 11/16 [2659]	137 13/16 [3501]	171 [4344]	204 3/16 [5186]	236 5/16 [6028]	270 1/2 [6871]	143 1/2 [3645]	212 11/16 [5402]	281 13/16 [7159]	351 [8916]	408 [10363]					
R.O.		Panel		Jamb																
		24 [610]	24 [610]	36 [914]	36 [914]	36 [914]	36 [914]	36 [914]	36 [914]	36 [914]	36 [914]	72 [1829]	72 [1829]	72 [1829]	72 [1829]	70 [1777]				
		Jamb																		
		7 3/8 [188]	10 3/8 [264]	7 3/8 [188]	10 3/8 [264]	13 3/8 [340]	16 3/8 [416]	19 3/8 [492]	22 3/8 [569]	25 3/8 [645]	7 3/8 [188]	10 3/8 [264]	13 3/8 [340]	16 3/8 [416]	19 3/8 [492]					
39 1/8 [994]	38 5/8 [981]	36 [914]		OX XO	OX XXO	OX XO	OX XXO	OXXX XXXO	OXXXX XXXXO	OXXXXX XXXXXO	OXXXXXX XXXXXXO	OXXXXXXX XXXXXXXO	OXXXXXXX XXXXXXXO	OXXXXXXX XXXXXXXO	OX XO	OX XXO	OXXX XXXO	OXXXX XXXXO	OXXXXX XXXXXO	OXXXXX XXXXXO
63 1/8 [1604]	62 5/8 [1591]	60 [1524]		OX XO	OX XXO	OX XO	OX XXO	OXXX XXXO	OXXXX XXXXO	OXXXXX XXXXXO	OXXXXXX XXXXXXO	OXXXXXXX XXXXXXXO	OXXXXXXX XXXXXXXO	OXXXXXXX XXXXXXXO	OX XO	OX XXO	OXXX XXXO	OXXXX XXXXO	OXXXXX XXXXXO	OXXXXX XXXXXO
87 3/16 [2214]	86 11/16 [2201]	84 [2134]				OX XO	OX XXO	OXXX XXXO	OXXXX XXXXO	OXXXXX XXXXXO	OXXXXXX XXXXXXO	OXXXXXXX XXXXXXXO	OXXXXXXX XXXXXXXO	OXXXXXXX XXXXXXXO	OX XO	OX XXO	OXXX XXXO	OXXXX XXXXO	OXXXXX XXXXXO	OXXXXX XXXXXO
99 1/8 [2518]	98 5/8 [2505]	96 [2438]				OX XO	OX XXO	OXXX XXXO	OXXXX XXXXO	OXXXXX XXXXXO	OXXXXXX XXXXXXO	OXXXXXXX XXXXXXXO	OXXXXXXX XXXXXXXO	OXXXXXXX XXXXXXXO	OX XO	OX XXO	OXXX XXXO	OXXXX XXXXO	OXXXXX XXXXXO	OXXXXX XXXXXO
111 1/8 [2823]	110 5/8 [2810]	108 [2743]				OX XO	OX XXO	OXXX XXXO	OXXXX XXXXO	OXXXXX XXXXXO	OXXXXXX XXXXXXO	OXXXXXXX XXXXXXXO	OXXXXXXX XXXXXXXO	OXXXXXXX XXXXXXXO	OX XO	OX XXO	OXXX XXXO	OXXXX XXXXO	OXXXXX XXXXXO	OXXXXX XXXXXO
123 1/8 [3128]	122 5/8 [3115]	120 [3048]				OX XO	OX XXO	OXXX XXXO	OXXXX XXXXO	OXXXXX XXXXXO	OXXXXXX XXXXXXO	OXXXXXXX XXXXXXXO	OXXXXXXX XXXXXXXO	OXXXXXXX XXXXXXXO	OX XO	OX XXO	OXXX XXXO	OXXXX XXXXO	OXXXXX XXXXXO	OXXXXX XXXXXO

- Minimum Panel Dimensions - 2' x 3'
- Maximum Panel Dimensions - 6' x 10'
- Maximum System Width - 34'

Note:

- O = Fixed
- X = Operating
- P = Pocketing
- The preparation of the rough opening for large openings such as those required by, but not limited to, LiftSlide, Bifold and MultiSlide doors have unique requirements. Structural headers that allow for deflection no greater than 1/8" along the unsupported length once the header is fully loaded are required. Special care needs to be taken when installing any unit including transoms above such large opening units.
- Loewen is not responsible for site measurements or the determination of structural and architectural requirements for the installation of large opening products such as but not limited to, LiftSlide, Bifold and MultiSlide doors. Site specifications are the responsibility of building professionals or engineers to determine.