

Multislide Narrow Stile - Stacking With Pocket

Width

Height	R.O	Rough Opening	53 [1346]	74 3/16 [1884]	77 [1956]	110 3/16 [2798]	143 5/16 [3640]	176 1/2 [4483]	209 5/8 [5325]	242 13/16 [6168]	276 [7010]	309 1/8 [7852]	149 [3784]	218 3/16 [5541]	287 5/16 [7298]	320 1/2 [8140]	409 [10389]		
		System	52 [1321]	73 3/16 [1858]	76 [1930]	109 3/16 [2773]	142 5/16 [3615]	175 1/2 [4457]	208 5/8 [5300]	241 13/16 [6142]	275 [6984]	308 1/8 [7827]	148 [3759]	217 3/16 [5516]	286 5/16 [7273]	319 1/2 [8115]	408 [1063]		
		Framed Rough Opening	28 [711]	49 3/16 [1249]	40 [1016]	73 3/16 [1858]	106 5/16 [2701]	139 1/2 [3543]	172 11/16 [4385]	205 13/16 [5228]	239 [6070]	272 1/8 [6913]	76 [1930]	145 3/16 [3687]	214 5/16 [5444]	247 1/2 [6286]	338 3/4 [8605]		
		Panel	24 [610]	24 [610]	36 [914]	36 [914]	36 [914]	36 [914]	36 [914]	36 [914]	36 [914]	36 [914]	36 [914]	36 [914]	72 [1829]	72 [1829]	72 [1829]	72 [1829]	69 1/4 [1758]
		Pocket	4 15/16 [125]	7 [178]	4 15/16 [125]	7 [178]	10 [254]	13 [330]	16 [406]	19 [483]	22 [559]	25 [635]	4 15/16 [125]	7 [178]	10 [254]	13 [330]	16 [406]		
		Jamb	4 3/8 [111]	7 3/8 [187]	4 3/8 [111]	7 3/8 [188]	10 3/8 [264]	13 3/8 [340]	16 3/8 [416]	19 3/8 [492]	22 3/8 [569]	25 3/8 [645]	4 3/8 [111]	7 3/8 [187]	10 3/8 [264]	13 3/8 [340]	16 3/8 [416]		
	39 1/8 [994]	38 5/8 [981]	36 [914]	PX XP	PXX XXP	PX XP	PXX XXP	PXXX XXXP	PXXXX XXXXP	PXXXXX XXXXXP	PXXXXXX XXXXXXP	PXXXXXXX XXXXXXXP	PX XP	PXX XXP	PXXX XXXP	PXXXX XXXXP	PXXXXX XXXXXP		
	63 1/8 [1604]	62 5/8 [1591]	60 [1524]	PX XP	PXX XXP	PX XP	OX XO	PXXX XXXP	PXXXX XXXXP	PXXXXX XXXXXP	PXXXXXX XXXXXXP	PXXXXXXX XXXXXXXP	PX XP	PXX XXP	PXXX XXXP	PXXXX XXXXP	PXXXXX XXXXXP		
	87 3/16 [2214]	86 11/16 [2201]	84 [2134]			PX XP	OX XO	PXXX XXXP	PXXXX XXXXP	PXXXXX XXXXXP	PXXXXXX XXXXXXP	PXXXXXXX XXXXXXXP	PX XP	PXX XXP	PXXX XXXP	PXXXX XXXXP	PXXXXX XXXXXP		
	99 1/8 [2518]	98 5/8 [2505]	96 [2438]			PX XP	OX XO	PXXX XXXP	PXXXX XXXXP	PXXXXX XXXXXP	PXXXXXX XXXXXXP	PXXXXXXX XXXXXXXP	PX XP	PXX XXP	PXXX XXXP	PXXXX XXXXP	PXXXXX XXXXXP		
	111 1/8 [2823]	110 5/8 [2810]	108 [2743]			PX XP	OX XO	PXXX XXXP	PXXXX XXXXP	PXXXXX XXXXXP	PXXXXXX XXXXXXP	PXXXXXXX XXXXXXXP	PX XP	PXX XXP	PXXX XXXP	PXXXX XXXXP	PXXXXX XXXXXP		
	123 1/8 [3128]	122 5/8 [3115]	120 [3048]			PX XP	OX XO	PXXX XXXP	PXXXX XXXXP	PXXXXX XXXXXP	PXXXXXX XXXXXXP	PXXXXXXX XXXXXXXP	PX XP	PXX XXP	PXXX XXXP	PXXXX XXXXP	PXXXXX XXXXXP		

- Minimum Panel Dimensions - 2' x 3'
- Maximum Panel Dimensions - 6' x 10'
- Maximum System Width - 34'

Note:

- O = Fixed
- X = Operating
- P = Pocketing
- The preparation of the rough opening for large openings such as those required by, but not limited to, LiftSlide, Bifold and MultiSlide doors have unique requirements. Structural headers that allow for deflection no greater than 1/8" along the unsupported length once the header is fully loaded are required. Special care needs to be taken when installing any unit including transoms above such large opening units.
- Loewen is not responsible for site measurements or the determination of structural and architectural requirements for the installation of large opening products such as but not limited to, LiftSlide, Bifold and MultiSlide doors. Site specifications are the responsibility of building professionals or engineers to determine.