

Multislide Wide Stile - Bi-Parting With Pocket

		Width										
R.O	Rough Opening	103 5/16 [2624]	142 9/16 [3621]	151 5/16 [3843]	214 9/16 [5450]	277 13/16 [7057]	341 1/16 [8664]	404 5/16 [10270]	295 5/16 [7501]	409 [10389]		
	System	102 5/16 [2599]	141 9/16 [3596]	150 5/16 [3818]	213 9/16 [5425]	276 13/16 [7032]	340 1/16 [8638]	403 5/16 [10244]	294 5/16 [7476]	408 [10363]		
	Framed Rough Opening	53 5/16 [1354]	92 9/16 [2351]	77 5/16 [1964]	140 9/16 [3571]	203 13/16 [5177]	267 1/16 [6784]	330 5/16 [8391]	149 5/16 [3793]	270 3/16 [6863]		
	Panel	24 [610]	24 [610]	36 [914]	36 [914]	36 [914]	36 [914]	36 [914]	72 [1829]	68 3/8 [1738]		
	Pocket	4 15/16 [125]	7 [178]	4 15/16 [125]	7 [178]	10 [254]	13 [330]	13 [330]	4 15/16 [125]	7 [178]		
	Jamb	4 3/8 [111]	7 3/8 [187]	4 3/8 [111]	7 3/8 [188]	10 3/8 [264]	13 3/8 [340]	16 3/8 [416]	4 3/8 [111]	7 3/8 [187]		
Height	39 1/8 [994]	38 5/8 [981]	36 [914]	PX:XP	PXX:XXP	PX:XP	PXX:XXP	PXXX:XXXP	PXXXX:XXXXP	PXXXXX:XXXXXP	PX:XP	PXX:XXP
	63 1/8 [1604]	62 5/8 [1591]	60 [1524]	PX:XP	PXX:XXP	PX:XP	PXX:XXP	PXXX:XXXP	PXXXX:XXXXP	PXXXXX:XXXXXP	PX:XP	PXX:XXP
	87 3/16 [2214]	86 11/16 [2201]	84 [2134]			PX:XP	PXX:XXP	PXXX:XXXP	PXXXX:XXXXP	PXXXXX:XXXXXP	PX:XP	PXX:XXP
	99 1/8 [2518]	98 5/8 [2505]	96 [2438]			PX:XP	PXX:XXP	PXXX:XXXP	PXXXX:XXXXP	PXXXXX:XXXXXP	PX:XP	PXX:XXP
	111 1/8 [2823]	110 5/8 [2810]	108 [2743]			PX:XP	PXX:XXP	PXXX:XXXP	PXXXX:XXXXP	PXXXXX:XXXXXP	PX:XP	PXX:XXP
	123 1/8 [3128]	122 5/8 [3115]	120 [3048]			PX:XP	PXX:XXP	PXXX:XXXP	PXXXX:XXXXP	PXXXXX:XXXXXP	PX:XP	PXX:XXP

- Minimum Panel Dimensions - 2' x 3'
- Maximum Panel Dimensions - 6' x 10'
- Maximum System Width - 34'

Note:

- O = Fixed
- X = Operating
- P = Pocketing
- The preparation of the rough opening for large openings such as those required by, but not limited to, LiftSlide, Bifold and MultiSlide doors have unique requirements. Structural headers that allow for deflection no greater than 1/8" along the unsupported length once the header is fully loaded are required. Special care needs to be taken when installing any unit including transoms above such large opening units.
- Loewen is not responsible for site measurements or the determination of structural and architectural requirements for the installation of large opening products such as but not limited to, LiftSlide, Bifold and MultiSlide doors. Site specifications are the responsibility of building professionals or engineers to determine.