

Multislide Wide Stile Stacking

		Width														
R.O	Rough Opening	47 [1193]	66 5/8 [1692]	71 [1803]	102 5/8 [2606]	134 1/4 [3410]	165 7/8 [4213]	197 1/2 [5016]	229 1/8 [5820]	260 3/4 [6623]	143 [3632]	210 5/8 [5349]	278 1/4 [7067]	345 7/8 [8785]	409 [10389]	
	System	46 [1168]	65 5/8 [1666]	70 [1777]	101 5/8 [2581]	133 1/4 [3384]	164 7/8 [4188]	196 1/2 [4991]	228 1/8 [5794]	259 3/4 [6598]	142 [3606]	209 5/8 [5324]	277 1/4 [7042]	344 7/8 [8760]	408 [10363]	
	Panel	24 [610]	24 [610]	36 [914]	36 [914]	36 [914]	36 [914]	36 [914]	36 [914]	36 [914]	36 [914]	72 [1829]	72 [1829]	72 [1829]	72 [1829]	61 11/16 [1567]
	Jamb	7 3/8 [188]	10 3/8 [264]	7 3/8 [188]	10 3/8 [264]	13 3/8 [340]	16 3/8 [416]	19 3/8 [492]	22 3/8 [569]	25 3/8 [645]	7 3/8 [188]	10 3/8 [264]	13 3/8 [340]	16 3/8 [416]	19 3/8 [492]	
	Height	39 1/8 [994]	38 5/8 [981]	36 [914]												
	63 1/8 [1604]	62 5/8 [1591]	60 [1524]													
	87 3/16 [2214]	86 11/16 [2201]	84 [2134]													
	99 1/8 [2518]	98 5/8 [2505]	96 [2438]													
	111 1/8 [2823]	110 5/8 [2810]	108 [2743]													
	123 1/8 [3128]	122 5/8 [3115]	120 [3048]													
				OX XO	OXX XXO	OX XO	OXX XXO	OXXX XXXXO	OXXXX XXXXXO	OXXXXX XXXXXXO	OXXXXXX XXXXXXXO	OXXXXXX XXXXXXXO	OXXXXXX XXXXXXXO	OXXXXXX XXXXXXXO	OXXXXXX XXXXXXXO	
				OX XO	OXX XXO	OX XO	OXX XXO	OXXX XXXXO	OXXXX XXXXXO	OXXXXX XXXXXXO	OXXXXXX XXXXXXXO	OXXXXXX XXXXXXXO	OXXXXXX XXXXXXXO	OXXXXXX XXXXXXXO	OXXXXXX XXXXXXXO	
						OX XO	OXX XXO	OXXX XXXXO	OXXXX XXXXXO	OXXXXX XXXXXXO	OXXXXXX XXXXXXXO	OXXXXXX XXXXXXXO	OXXXXXX XXXXXXXO	OXXXXXX XXXXXXXO	OXXXXXX XXXXXXXO	
						OX XO	OXX XXO	OXXX XXXXO	OXXXX XXXXXO	OXXXXX XXXXXXO	OXXXXXX XXXXXXXO	OXXXXXX XXXXXXXO	OXXXXXX XXXXXXXO	OXXXXXX XXXXXXXO	OXXXXXX XXXXXXXO	
						OX XO	OXX XXO	OXXX XXXXO	OXXXX XXXXXO	OXXXXX XXXXXXO	OXXXXXX XXXXXXXO	OXXXXXX XXXXXXXO	OXXXXXX XXXXXXXO	OXXXXXX XXXXXXXO	OXXXXXX XXXXXXXO	

- Minimum Panel Dimensions - 2' x 3'
- Maximum Panel Dimensions - 6' x 10'
- Maximum System Width - 34'

Note:

- O = Fixed
- X = Operating
- P = Pocketing
- The preparation of the rough opening for large openings such as those required by, but not limited to, LiftSlide, Bifold and MultiSlide doors have unique requirements. Structural headers that allow for deflection no greater than 1/8" along the unsupported length once the header is fully loaded are required. Special care needs to be taken when installing any unit including transoms above such large opening units.
- Loewen is not responsible for site measurements or the determination of structural and architectural requirements for the installation of large opening products such as but not limited to, LiftSlide, Bifold and MultiSlide doors. Site specifications are the responsibility of building professionals or engineers to determine.