

### Multislide Wide Stile Stacking with Pocket Door Detail

Width

<b>Height</b>	<b>R.O</b>	<b>Rough Opening</b>	53 [1346]	72 5/8 [1845]	77 [1956]	108 5/8 [2759]	140 1/4 [352]	171 7/8 [4366]	203 1/2 [5169]	235 1/8 [5973]	266 3/4 [6776]	298 3/8 [7579]	149 [3784]	216 5/8 [5502]	284 1/4 [7220]	351 7/8 [8938]	409 [10389]	
		<b>System</b>	52 [1321]	71 5/8 [1819]	76 [1930]	107 5/8 [2734]	139 1/4 [3537]	170 7/8 [4340]	202 1/2 [5144]	234 1/8 [5947]	265 3/4 [6751]	297 3/8 [7554]	148 [3759]	215 5/8 [5477]	283 1/4 [7195]	350 7/8 [8912]	408 [1063]	
		<b>Framed Rough Opening</b>	28 [711]	47 5/8 [1210]	40 [1016]	71 5/8 [1819]	103 1/4 [2623]	134 7/8 [3426]	166 1/2 [4229]	198 1/8 [5033]	229 3/4 [5836]	261 3/8 [6640]	76 [1930]	143 5/8 [3648]	211 1/4 [5366]	278 7/8 [7084]	337 3/4 [8579]	
		<b>Panel</b>	24 [610]	24 [610]	36 [914]	36 [914]	36 [914]	36 [914]	36 [914]	36 [914]	36 [914]	36 [914]	36 [914]	72 [1829]	72 [1829]	72 [1829]	72 [1829]	70 1/4 [1784]
		<b>Pocket</b>	4 15/16 [125]	7 [178]	4 15/16 [125]	7 [178]	10 [254]	13 [330]	16 [406]	19 [483]	22 [559]	25 [635]	4 15/16 [125]	7 [178]	10 [254]	13 [330]	16 [406]	
		<b>Jamb</b>	4 3/8 [111]	7 3/8 [187]	4 3/8 [111]	7 3/8 [188]	10 3/8 [264]	13 3/8 [340]	16 3/8 [416]	19 3/8 [492]	22 3/8 [569]	25 3/8 [645]	4 3/8 [111]	7 3/8 [187]	10 3/8 [264]	13 3/8 [340]	16 3/8 [416]	
	39 1/8 [994]	38 5/8 [981]	36 [914]	PX XP	PXX XXP	PX XP	PXX XXP	PXXX XXXXP	PXXXX XXXXXP	PXXXXX XXXXXP	PXXXXXX XXXXXP	PXXXXXXX XXXXXP	PX XP	PXX XXP	PXXX XXXP	PXXXX XXXXP	PXXXXX XXXXXP	
	63 1/8 [1604]	62 5/8 [1591]	60 [1524]	PX XP	PXX XXP	PX XP	OXX XXO	PXXX XXXP	PXXXX XXXXP	PXXXXX XXXXXP	PXXXXXX XXXXXP	PXXXXXXX XXXXXP	PX XP	PXX XXP	PXXX XXXP	PXXXX XXXXP	PXXXXX XXXXXP	
	87 3/16 [2214]	86 11/16 [2201]	84 [2134]			PX XP	OXX XXO	PXXX XXXP	PXXXX XXXXP	PXXXXX XXXXXP	PXXXXXX XXXXXP	PXXXXXXX XXXXXP	PX XP	PXX XXP	PXXX XXXP	PXXXX XXXXP	PXXXXX XXXXXP	
	99 1/8 [2518]	98 5/8 [2505]	96 [2438]			PX XP	OXX XXO	PXXX XXXP	PXXXX XXXXP	PXXXXX XXXXXP	PXXXXXX XXXXXP	PXXXXXXX XXXXXP	PX XP	PXX XXP	PXXX XXXP	PXXXX XXXXP	PXXXXX XXXXXP	
	111 1/8 [2823]	110 5/8 [2810]	108 [2743]			PX XP	OXX XXO	PXXX XXXP	PXXXX XXXXP	PXXXXX XXXXXP	PXXXXXX XXXXXP	PXXXXXXX XXXXXP	PX XP	PXX XXP	PXXX XXXP	PXXXX XXXXP	PXXXXX XXXXXP	
	123 1/8 [3128]	122 5/8 [3115]	120 [3048]			PX XP	OXX XXO	PXXX XXXP	PXXXX XXXXP	PXXXXX XXXXXP	PXXXXXX XXXXXP	PXXXXXXX XXXXXP	PX XP	PXX XXP	PXXX XXXP	PXXXX XXXXP	PXXXXX XXXXXP	

- Minimum Panel Dimensions - 2' x 3'
- Maximum Panel Dimensions - 6' x 10'
- Maximum System Width - 34'

**Note:**

- O = Fixed
- X = Operating
- P = Pocketing
- The preparation of the rough opening for large openings such as those required by, but not limited to, LiftSlide, Bifold and MultiSlide doors have unique requirements. Structural headers that allow for deflection no greater than 1/8" along the unsupported length once the header is fully loaded are required. Special care needs to be taken when installing any unit including transoms above such large opening units.
- Loewen is not responsible for site measurements or the determination of structural and architectural requirements for the installation of large opening products such as but not limited to, LiftSlide, Bifold and MultiSlide doors. Site specifications are the responsibility of building professionals or engineers to determine.